

### 3000 Series Cooler - Sample Conditioning Plate - Integration Options

Lead Time	Integration Options						
3 wks	SCP	Integrate 3000 cooler on a powder coated plate with accessories selected below					
	SCU	Integrate 3000 cooler in a U-Bracket with accessories selected below					
<b>Cooler (Part Number Configurator: SCP 3000)</b>							
<b>Sample Conditioning Plate</b>							
	<b>3040</b>	One 10" Heat Exchanger, (1) Active, (1) Sample Stream					
	<b>3050</b>	Two 10" Heat Exchangers (1) Passive/(1) Active, (1) Sample Stream					
	<b>3080</b>	Two 10" Heat Exchangers (2) Active, (1) or (2) Sample Streams					
<b>Heat Exchangers Material (Price per Heat Exchanger)</b>							
	<b>SS</b>	316 Stainless Steel: (Inner and Outer)					
	<b>PV</b>	Glass/Kynar: (Kynar Inner/Glass Outer)					
	<b>C</b>	Hastelloy C276: (316SS Inner/C276 Outer)					
	<b>CC</b>	Hastelloy C276: (Inner and Outer)					
+1 wk	<b>ST</b>	Teflon coated 316 Stainless Steel:					
	<b>SW</b>	316 Welded Stainless Steel: (High Pressure)					
	<b>SN</b>	SilcoNert™ 2000 coated 316 Stainless Steel:					
	<b>KK</b>	Kynar/ Kynar: (Inner and Outer)					
<b>Voltage &amp; Area Location Classification</b>							
	<b>115</b>	115 VAC 50/60 Hz; General Purpose (GP) Area					
+1 wk	<b>230</b>	230 VAC 50/60 Hz; General Purpose (GP) Area					
	<b>Sample Pump with one pressure controller.</b>						
	<b>SP1</b>	Single Head Pump					
	<b>SP2</b>	Dual Head Pump					
<b>Calibration Gas Solenoids (Standard panel includes two calibration gas solenoids)</b>							
	<b>Cal2</b>	No Additional Calibration Gas Solenoids (Base Panel Includes 2)					
	<b>Cal3</b>	1 Additional Calibration Gas Solenoid (3 Total)					
	<b>Cal4</b>	2 Additional Calibration Gas Solenoid (4 Total)					
	<b>Cal5</b>	3 Additional Calibration Gas Solenoid (5 Total)					
	<b>Cal6</b>	4 Additional Calibration Gas Solenoid (6 Total)					
<b>Analyzer Flow Meter Options</b>							
	<b>FM1</b>	1 Base Panel 2.5lpm Flow Meter = Panel with 1 Analyzer Meter, 1 Bypass Meter, 1 Cal Gas Meter					
	<b>FM2</b>	1 Additional 2.5 lpm Flow Meter = Panel with 2 Analyzer Meters, 1 Bypass Meter, 1 Cal Gas Meter					
	<b>FM3</b>	2 Additional 2.5 lpm Flow Meter = Panel with 3 Analyzer Meters, 1 Bypass Meter, 1 Cal Gas Meter					
	<b>FM4</b>	3 Additional 2.5 lpm Flow Meter = Panel with 4 Analyzer Meters, 1 Bypass Meter, 1 Cal Gas Meter					
<b>Peristaltic Tubing Options</b>							
+1 wk	<b>PP1</b>	Phar-Med High Pressure Pump Tubing					
	<b>PP2</b>	Viton Pump Tubing					
	<b>PP3</b>	Tygon Fuel Grade Tubing					
	<b>PP4</b>	Norprene Food Grade Tubing					
	<b>N</b>	Standard Tubing					
SCP	3080	-SS	-115	-SP1	-Cal2	-FM1	-N

\* Lead Times are not compounded. Lead time is Cooler + longest option.

**Black Powder Coated Plate or U-Bracket Includes:**

- Sample pump
- Peristaltic Pump
- Inline Filter with Condensate Carry Over Sensor
- Pressure Gauge
- Vacuum Gauge
- Alarm Switches
- Calibration Gas Regulator
- Calibration Gas Solenoid Valves
- Analyzer, Bypass and Calibration Gas Flow Meters